


Coaxial Cables (75 ohms)
JIS C-3501
Description:

High frequency Coaxial cable, copper or tinned copper conductor, PE or Foam PE insulation and copper or tinned copper braided shield.

Coaxial Cable Type	Number & Diameter of wire mm	Insulation Thickness mm	Sheath Thickness mm	Cable Diameter Approx. mm	Total Weight Approx. kg/km	Attenuation 10 MHz dB/Km	Impedance ohms
3 C - 2 V	1 x 0.5	1.3	0.8	5.4	42	42	75
★4.5 C - 2 V	1 x 1.0	1.75	0.6	6.4	47	22	75
5 C - 2 V	1 x 0.8	2.05	0.9	7.4	74	27	75
5 C - 2 W	1 x 0.8	2.05	1.0	8.3	120	27	75
7 C - 2 V	7 x 0.4	3.05	1.1	10.4	140	22	75
10 C - 2 V	7 x 0.5	3.95	1.3	13.1	220	18	75

1-Stranded Circular or Solid Conductor 2-PE or Foam PE Insulation 3-Copper or Tinned Copper Shield 4-PVC Sheathing.

★: With Foamed PE Insulation

 Impedance 75 ohm and Capacitance 67 ± 3 nf/Km

Coaxial cables are used in high frequency transmission, specially for transmitters and receivers, computers, radio and TV transmissions. The varied mechanical, thermal and electronic properties of coaxial cables mean that they can be used up into the GHz levels.