

Cu/PVC/PVC

BS 6004

Description :

Flat twin core cable, with uninsulated circuit-protective conductor and cores shall be laid parallel.

Number of Cores & Cross mm ²	Insulation Thickness mm	* Sheath Thickness		Cable Dimension		Total Weight Approx. kg/km
		e ₁ mm	e ₂ mm	Width mm	Thickness mm	
2 x 1 + 1.0 RE	0.6	1.0	0.9	7.6	4.3	71
2 x 1.5 + 1.0 RE	0.7	1.0	0.9	8.7	4.8	90
2 x 1.5 + 1.0 RM	0.7	1.0	1.0	9.5	5.0	97
2 x 2.5 + 1.5 RE	0.8	1.1	1.0	10.6	5.6	133
2 x 2.5 + 1.5 RM	0.8	1.1	1.0	11.2	5.8	140
2 x 4 + 1.5 RM	0.8	1.1	1.0	12.9	6.4	183
2 x 6 + 2.5 RM	0.8	1.2	1.1	14.8	7.1	252
2 x 10 + 4.0 RM	1.0	1.3	1.2	18.6	8.7	398
2 x 16 + 6.0 RM	1.0	1.4	1.3	20.7	9.5	547

1-Solid or Stranded Circular Conductor 2-Circuit-Protective Conductor 3-PVC Insulation 4-PVC Sheathing.

* : e₁, e₂ As FIG. 2




FIG. 2 - Cross-section of Cable