

Cu/PVC/PVC

BS 6004

Description :

Flat 3-core cable, with uninsulated circuit-protective conductor and cores shall be laid parallel.

Number of Cores & Cross mm^2	Insulation Thickness mm	* Sheath Thickness		Cable Dimension		Total Weight Approx. kg/km
		e_1 mm	e_2 mm	Width mm	Thickness mm	
3 x 1 + 1.0 RE	0.6	1.0	0.9	9.9	4.3	93
3 x 1.5 + 1.0 RE	0.7	1.0	0.9	11.5	4.8	121
3 x 2.5 + 1.5 RE	0.8	1.1	1.0	13.9	5.6	175
3 x 4 + 1.5 RM	0.8	1.2	1.1	17.2	6.6	257
3 x 6 + 2.5 RM	0.8	1.3	1.1	19.5	7.3	350
3 x 10 + 4.0 RM	1.0	1.4	1.2	24.6	8.9	555
3 x 16 + 6.0 RM	1.0	1.5	1.3	27.4	9.7	764

1-Solid or Stranded Circular Conductor 2-Circuit-Protective Conductor 3-PVC Insulation 4-PVC Sheathing.

* : e_1 , e_2 As FIG. 4




FIG. 4 - Cross-section of Cable